



# Introducing the New Glass Front Vendor GF9-H

- New Vertically-oriented X-Rail allows any dropped products to pass without service interruption
- New Fully Adjustable Product Shelves allow maximum product selectivity and capacity
- New Magnetic Door Gasket provides superior effortless sealing and locking functions
- Separate smooth sliding side drawer allows for easy access to all electrical components and payment systems without having to open the product loading door, and preventing the introduction of warm air into the cabinet
- New Stronger Cabinet design includes increased Insulation thickness, one pieced Base construction, and a Reinforced Slide Cabinet to allow use of "Squeeze" lifts for movement in the warehouse
- New Redesigned Refrigeration System results in reduced energy consumption and improved pull-down/reload recovery time while retaining its easy access for serviceability
- Now comes standard with Low GWP R290 (Propane) Natural Refrigerant (GWP=3)
- Refrigerant Charge Size  $\leq 114g$  allows unrestricted placement opportunities
- Extendable Product Trays promotes First-in First-Out (FIFO) product loading to ensure next to vend
- Tough vandal-resistant metal selection keypad
- Spacers available for oddly shaped and/or top-heavy packages
- Meets both DOE and Energy Star requirements



**GF9-H**





# FEATURES & SPECIFICATIONS

## Introducing the New Glass Front Vendor GF9-H

GF9-H	
Total Can Capacity with 7 Shelves	567
Total Pet Bottle Capacity with 5 Shelves	360
# of Selections with 7 Shelves	63
# of Selections with 5 Shelves	45
Dimensions* - H x W x D	72" x 47" x 34"
Shipping Weight*	715 lbs.
Operations Voltage	120V 60Hz
Amp Rating	8
Energy Consumption (DOE)	3.97 kWh/day
Lighting	LED
Refrigerant	R-290
Lock Type	T-Handle
Capacity per Selection	
12oz. Can	9
8 oz./250 ml Can	11
16 oz./20 oz. PET Bottle**	8
11 oz./12 oz. "SLIM" Can	10

\*Dimensions and shipping weight will vary slightly.  
 \*\*Product capacities will vary based on package dimensions



The GF9-H meets the current Americans with Disabilities Act 2010 Standard for Accessible Design. The reach range requirements have been changed to provide that the side reach range must now be no higher than 48 inches (instead of 54 inches) and no lower than 15 inches (instead of 9 inches)



At Sanden Vendo America, we take our commitment to the environment very seriously. That's why we're proud to offer our full range of vending machines charges with low GWP alternate refrigerant. All models are cUL listed and meet or exceed DOE requirements. R290 is a safe refrigerant with zero Ozone Depleting Potential and a Global Warming Potential (GWP) of 3.



The GF9-H meets or exceeds the department of Energy 2019 Efficiency Standards.



Sanden Vendo America, Inc offers a complete line of parts, accessories, supplies, and add on security devices. Call for more information:

SandenVendo America, Inc P: 214-765-9066 F: 214-340-8028  
 10710 Sanden Drive, Dallas, TX 75238 P: 800-344-7216 F: 800-541-5684

